

REBLOC RB80XA_8

Standard element




Application
Permanent system

Installation
Free standing



Containment level **N2** (covers N1, T2 and T1)
 Working width **W3** (covers W4, W5, W6, W7 and W8)
 Impact severity level **ASI B**



Precast concrete vehicle restraint systems are used for long lasting protection on the central reservation and along the verge. Vehicles deviating from the road are retained or redirected and prevent a dangerous breakthrough onto the opposite carriageway. As a result road users and persons as well as objects at the roadside are well protected.

The integrated, innovative coupling together with a full-length steel tension bar and an ingeniously-designed reinforcement system ensure high security and practicality. The single elements are connected to a strong chain, which safely dissipates the energy caused by vehicle impact.

Thanks to the interlocking coupling, there are no loose parts, which prevent unauthorized removal of pieces and protects fully against vandalism.


REBLOC RB80XA-8

Standard element

N2

W3

Technical data



all dimensions in mm

Containment level	N2
Working width	W3
Impact severity level	ASI B
Installation	free standing on asphalt/concrete
Terminal elements	required; REBLOC 80X_4T (2 x M24 adhesive anchors)
Dimensions L x W x H in mm	8000 x 590 x 800 mm
Weight/element (approx.)	4600 kg
Elements/truck (24 t)	5 elements
Minimum installation length	112 m
Curve radius	$r \geq 250$ m, smaller radii on request
Coupling/exposed steel parts	fully integrated, exposed parts hot-dip galvanized
CE certification	✓